

# brands you trust.



## Solutions for Power Generation



www.cranecpe.com



# Index

Introduction to Crane Co.	
Quality and Certifications	5
Combined Cycle Power Plant	
Coal-fired Power Plant	8–9
Solar and Geothermal Power	
Wet Flue Gas Desulfurization	
Isolation Valves	
Flow Reversal Protection Valves	
Special Application Valves	
Polypropylene-Lined Pipe and Fittings	
Global Coverage	20–21
Delivery Systems	

## Introduction to Crane • Crane Co.

# FOUNDED IN 1855

- FLUID HANDLING
- 2 AEROSPACE & ELECTRONICS
- 3 MERCHANDISING SYSTEMS AND PAYMENT TECHNOLOGIES
- ENGINEERED MATERIALS

### Crane Co.

Crane Co. is a diversified global manufacturer of engineered industrial products traded on the New York Stock Exchange (NYSE: CR). One of its segments, Crane Fluid Handling, provides highly engineered products for fluid handling applications worldwide.

### **The Fluid Handling Segment**


Crane Fluid Handling provides highly-engineered products including **valves**, **pumps**, **controls and water treatment equipment for fluid handling applications worldwide.** Its operating units include Crane ChemPharma & Energy, Crane Nuclear, Crane Building Services, Crane Pumps & Systems, Crane Supply, Barksdale Control Products.

## Crane ChemPharma & Energy (CPE)


Crane CP&E designs and manufactures a variety of highperformance products including: highly-engineered **check valves, sleeved plug valves, lined valves, process ball valves, high performance butterfly valves**, bellows sealed globe valves, aseptic and industrial diaphragm valves, multi/ quarter-turn valves, actuation, sight glasses, lined pipe, **fitting and hoses, and air-operated diaphragm and peristaltic pumps**. Its trusted brands are in use worldwide in many industries, including Oil & Gas, Oil Refining, Petrochemical, Power Generation, Chemical Processing, Biotechnology, and Pharmaceutical.

## Crane (CPE) Brands

ALOYCO · CENTER LINE · COMPAC-NOZ · CRANE · DEPA DUO-CHEK · ELRO · FLOWSEAL · JENKINS · KROMBACH NOZ-CHEK · PACIFIC · RESISTOFLEX · REVO · SAUNDERS STOCKHAM · TRIANGLE · UNI-CHEK · WTA · XOMOX



### **Key Markets**



## **Quality & Certifications**




The following is a partial list of certificates held by Crane ChemPharma & Energy. All certificates are available upon request.

- ISO 15848-1
- ASME 16.34, 16.10, 16.5, 16.25
- ISO 9001: 2000 (Det Norske Veritas, TÜV)
- ISO 14001:2005 (TÜV Nord)
- Zertifikat DGRL Certificate PED (TÜV Nord)
- Directive 97/56/EG
- API 6D
- QS Certificate of Assessment PED (Det Norske Veritas)
- Technical Standards & Safety Authority
- Laboratorio De Pruebas De Equipos Y Materiales
- Welding Procedure Approval (Det Norske Veritas)
- Russian GOST R
- Water Regulation Advisory Scheme
- Design Assessement (American Bureau of Shipping)
- Konformitätserklärung ATEX -Declaration of Conformity ATEX
- DVGW Baumuster-Prüfzertifikat Gasversorgung (DVGW Zertifizierungsstelle)
- Certificate of Recognition (Bureau Veritas)
- AD 2000-Merkblatt HP 0/TRD 201/GGVE/GGVS
- \*\* These certifications are only applicable to certain products.

- AD 2000-Merkblatt A4
- Shipbuilding approval according to MODE IBV/Mode II
- EN 729-2
- KTA 1401
- TA Luft 2000
- API 622 emissions testing
- EPA Method 21 emissions testing
- CE
- 10CFR50 Appendix B
- ASME N45.2
- ASME N-Stamp N-2 899
- ASME NPT Stamp N-2900
- ASME NCA-4000
- ASME NB Registration
- Repair and Testing of Valves and Actuators in Compliance with 10CFR.50 Appendix B and ASME NQA-1
- "NR"- Field Repair or Replacement of Class
  1, 2, & 3 Line Valves and Section III Class
  1, 2 and 3 Pressure Relief Devices
- "VR"- Field Repair of ASME Section I, III and VIII PRV



## **Combined Cycle Power Plant**



### 5. Cooling Water Circulation

Butterfly Valves Check Valves Isolation Valves Drain Valves Diaphragm Valves Polypropylene-Lined Pipe

### 6. Water Treatment

Butterfly Valves Check Valves Isolation Valves Drain Valves Diaphragm Valves Polypropylene-Lined Pipe

#### 7. Condensate Pumps

Butterfly Valves Check Valves Isolation Valves Drain Valves

### 8. Heat Exchanger

Check Valves Isolation Valves Vent & Drain Valves


#### 9. Make-up Water

Butterfly Valves Check Valves Isolation Valves Lined Valves Strainers Diaphragm Valves Polypropylene-Lined Pipe

#### 10. Deaerator

Check Valves Isolation Valves Vent & Drain Valves Diaphragm Valves

## **Combined Cycle Power Plant**



#### 11. LP Drum Deaerator

Check Valves Isolation Valves Vent & Drain Valves

#### 12. Process & Export Steam

Check Valves Isolation Valves Vent & Drain Valves

#### 13. Feed Water Distribution (HP, IP, LP)

Butterfly Valves Check Valves Isolation Valves Metal Seated Ball Valves

#### 14. Economizers (HP, IP, LP)

Check Valves Isolation Valves Vent & Drain Valves Metal Seated Ball Valve

#### 15. Flash Tank

Check Valves Isolation Valves Vent & Drain Valves

#### 16. SCR Storage & Injection

Butterfly Valves Check Valves Isolation Valves

## **Coal-fired Power Plant**

#### 1. Drums

Check Valves Isolation Valves Non-return Valves Vent & Drain Valves

#### 2. Superheater

Check Valves Isolation Valves Vent & Drain Valves

#### 3. Reheater

Check Valves Isolation Valves Extraction Check Valves Vent & Drain Valves

**4.** Steam Turbine w/ Condenser Drain Valves Extraction Check Valves Main Steam Isolation

#### 5. Cooling Water Circulation

Check Valves Isolation Valves Butterfly Valves Drain Valves Diaphragm Valves Polypropylene-Lined Pipe

#### 6. Water Treatment


Butterfly Valves Check Valves Isolation Valves Drain Valves Diaphragm Valves Polypropylene-Lined Pipe

#### 7. Condensate Pumps

Check Valves Isolation Valves Drain Valves

#### 8. Heat Exchanger

Check Valves Isolation Valves Vent & Drain Valves



9. Low Pressure Heaters Check Valves Isolation Valves

#### 10. Deaerator


Check Valves Isolation Valves Vent & Drain Valves Diaphragm Valves Polypropylene-Lined Pipe **11. Evaporator** Check Valves Isolation Valves Vent & Drain Valves

#### 12. Make-up Water

Check Valves Isolation Valves Vent & Drain Valves Strainers Diaphragm Valves Polypropylene-Lined Pipe



## **Coal-fired Power Plant**



26. Ash Handling Isolation Valves **Diaphragm Valves** Polypropylene-Lined Pipe

#### 19. Bag House Isolation Valves

20. Scrubber Isolation Valves

Check Valves **Isolation Valves** 

Check Valves **Isolation Valves** Vent & Drain Valves

Check Valves Isolation Valves

Check Valves

Check Valves **Isolation Valves** 

Check Valves **Isolation Valves** 

Isolation Valves


Extraction Check Valves

Vent & Drain Valves Metal Seated Ball Valves


21. Precipitator Isolation Valves

## **Solar & Geothermal Power**


### **Concentrated Solar Power - Tower Technology**



## **Geothermal Power Binary Cycle**



# Wet Flue Gas Desulfurization



## **Isolation Valves Pressure Seal**

### **Pressure Seal Gate**

Brand: Aloyco, Crane, Krombach, Pacific ASME Class: 600 - 4500 Sizes: 2½" - 36" DN: 65 - 900 Materials: Carbon Steel, Stainless Steel & Alloy. Cast and Forged Connections: Weld End, Flanged, Venturi

### **Features & Benefits:**

- · Gate valves offered in two designs: parallel disc and flexible wedge
- Provides superior shutoff service for your high pressure and temperature applications
- The parallel disc gate valve eliminates excessive leakage, thermal binding and maintenance with:
  - 1. Spring-loaded discs that seal with differential pressure and self adjust for thermal growth and pipe stresses the higher the differential pressure the tighter the seal
  - 2. Integrally cast body stops that eliminate over travel and prevent wire drawing or steam cutting of seats
  - 3. Fully guided carrier assembly which is position seated rather than torque seated
  - 4. Parallel seating components that are hard-faced and self cleaning, ensuring extended life
  - 5. Lower torque requirements allowing smaller actuation packages
  - 6. Easy in-line repair and fitting



## **Pressure Seal Globe**

Brand: Aloyco, Crane, Krombach, Pacific ASME Class: 600 - 4500 Sizes: 8" - 24" (Y-Globe) 2"-12" (T-Globe) DN: 65 - 600 Materials: Carbon Steel, Stainless Steel & Alloy. Cast & Forged Connections: Weld End, Flanged, Venturi

### **Features & Benefits:**

- Available in both y-pattern and t-pattern, as well as both globe stop and stop-check (non-return) configurations, bodies with streamlined flow path to minimize pressure drop
- Fully body-guided discs for perfect seating in high pressure service
- Disc, seat rings, and backseat have hardened surfaces for maximum service life
- Stainless steel, precision ground stems to minimize packing friction
- Two-piece, self-aligning glands
- Fully fabricated yokes designed to withstand seismic activity, while offering easy maintenance and actuator mounting
- Hammerblow handwheel standard
- Best in class flow characteristics (Cv) for Y-Globe valves



## **Isolation Valves Bolted Bonnet**

## **Bolted Bonnet Gate**

Brands: Aloyco, Crane, Krombach, Pacific ASME Class: 150 - 1500 Sizes: 2" - 36" Materials: Carbon Steel, Stainless Steel, Alloy Connections: Weld End, Flanged, Threaded

### **Features & Benefits:**

- Body is cast with straight through ports to minimize turbulence, erosion and pressure drop are minimized
- Seat rings are seal welded to eliminate leak path behind rings and for long trouble-free service
- Our one piece flexible disc provides accurate alignment of mating seating surfaces so the valve can absorb piping strains without leakage and avoids any tendency to stick in the seated position
- Packing contains corrosion inhibitor to avoid stem pitting
- Stuffing box is deep, assuring long packing life
- Gland Eyebolts swing aside for ease in repacking the stuffing box
- API 624 available



## **Bolted Bonnet Globe**

Brands: Aloyco, Crane, Krombach, Pacific ASME Class: 150–1500 Sizes: 2" - 24" Materials: Carbon Steel, Stainless Steel, Alloy Connections: Weld End, Flanged

### **Features & Benefits:**

Available in globe stop configurations. Our globe valves are designed for services requiring frequent operation and throttling when pressure drop across the valve is about 20% of inlet pressure.

- Body is designed with heavy sections reinforced at points subjected to the greatest stress
- Seat ring welded in to eliminate leak path in cast steel design
- Disc stem ring connects the disc to the stem, permitting the disc to swivel and aid in securing tight seating for trouble-free service
- Gland eyebolts are securely fastened to the bonnet yet swing away to permit easy access to the stuffing box
- API 623 available



## **Flow Reversal Protection Valves**

## **Pressure Seal Check**

Brand: Aloyco, Crane, Krombach, Pacific ASME Class: 600 - 3500 Sizes: 2 1/2" - 36" DN: 65 - 900 Materials: Carbon Steel, Stainless Steel, Alloy Connections: Weld End, Flanged

### Valve Types:

Swing Check, Tilting Disc (Non-Slam), Y-Pattern Lift, and T-Pattern Lift Configurations

- The tilting disc check valve uses gravity to rapidly close the disc upon flow reversal (Non-Slam)
- Valve design fully opens or closes through an arc of only 45 degrees, (unlike most other tilting disc check valves which must swing through a 90 degree arc)
- Conical seating is self aligning, tight, and always closed in a no-flow situation
- Hard-faced seating surfaces, large diameter hinge pins, and corrosion resistant bearing surfaces ensure long life, and an internal disc stop prevents flutter
- The internal disc hanger provides adjustable alignment and eliminates body wall penetrations

## **Bolted Bonnet Swing Check**

Brands: Aloyco, Crane, Krombach, Pacific ASME Class: 150–1500 Sizes: 2" - 36" Materials: Cast Iron, Carbon Steel, Stainless Steel, Alloy, Forged Steel Connections: Weld End, Flanged

### **Features & Benefits:**

- Used to prevent reversal of flow in horizontal pipe lines
- There is no tendency for the seating surfaces to gall or score, because the disc meets the flat seat squarely without rubbing contact upon closing
- Can be furnished with outside lever and adjustable weight in certain sizes, to assist in closing the valve more rapidly, thus minimizing reversal of flow and resultant surge and shock
- With the lever and weight mounted to balance the weight of the disc, the valve becomes more sensitive to low flow velocities





# **Flow Reversal Protection Valves**

### Nozzle Check (Compact & Full Body)

Brands: Compac-Noz, Noz-Chek ASME Class: 150 - 4500 Sizes: 2" - 84" DN: 50 - 2100 Materials: Ductile Iron, Carbon Steel, Stainless Steel, Alloy Connections: Flanged, Hub-End, Weld-End Standards: ASME, DIN, JIS

#### **Features & Benefits:**

- Engineered and sized for the application, not the line size
- One piece body casting (no body penetration, no fugitive emission to atmosphere)
- One moving part resulting in minimum wear and long life
- Short stroke length resulting in quick dynamic response and minimizing the reverse velocity through the valve, thus preventing water hammer risks
- Suitable for reciprocating compressor service (removal of chatter effects frequently associated with conventional check valves)
- Stable behavior due to the Venturi type design, the opening characteristics ensure a fully opened check valve
- Choice of spring torques to suit critical velocity systems and improve valve response time
- Anti-spinning device to stabilize disc
- Tight shut-off
- Maintenance free design

### **Dual Plate Check**

Brands: Duo-Chek ASME Class: 125 - 4500 Sizes: 2" - 84" DN: 50 - 2100 Materials: Cast Iron, Bronze, Carbon Steel, Stainless Steel, Alloy Connections: Wafer, Lugged, Flanged Standards: ASME, DIN, JIS, AS

#### **Features & Benefits:**

- Lightweight & compact compared to the traditional swing check valve
- Spring assisted closure (independent spring design), plates are more responsive to changes in flow conditions
- Faster response time improved by the use of independent springs and support sleeves, minimizes water hammer risks for non slam applications
- Retainerless design available (no fugitive emission to atmosphere, valve is inherently fire-safe)
- Choice of spring torques to suit critical velocity systems and improve valve response time





CRANE

# **Special Application Valves**

## **Resilient-Seated Concentric Butterfly**

Brands: Center Line, CRANE, Krombach ASME Class: 150 CWP Sizes: 1½" - 54" DN: 40 - 1350 Materials: Cast Iron, Ductile Iron, Carbon Steel, Stainless Steel Body Styles: Wafer, Lugged, Double Flanged

### **Features & Benefits:**

- Qualified for both gaseous and liquid service
- Positive shut-off bi-directionally
- Phenolic backed cartridge seat
- PTFE bushing standard
- Locking handle standard (2"-12")
- End of line service standard on lug style
- Ease of automation
- Field repairable (2"-24")
- Complete size range: 11/2" 54"



## **High Performance Butterfly**

Brands: Flowseal, Xomox ASME Class: 150 - 600 Sizes: 2" - 48" DN: 50 - 1200 Materials: Carbon Steel, Stainless Steel & Alloy Body Styles: Wafer, Lugged (Double Dead End)

### **Features & Benefits:**

- Soft seat design provides bubble tight shut-off
- Metal seated; ASME Class IV Leakage
- Wafer and lug body styles
- Firesafe, Meets API 607, Rev. 4
- MSS-SP-68
- Unparalleled service in vacuum-to-low pressure



# **Special Application Valves**

## **Double Eccentric Butterfly**

Brands: Krombach ASME Class: 150 - 600 PN: 10 - 40 Sizes: 4" - 136" DN: 100 - 3400 Materials: Ductile Iron, Carbon Steel Body Styles: Double Flanged Short or Long Pattern, Custom Ends

### **Features & Benefits:**

- Fabricated body, resilient seated
- Soft seat design provides tight shut-off
- Optimal flow profile of disc
- Hard rubber coating for heavy duty installations possible



## **Triple Offset**

Brands: CRANE®FKX 9000 ASME Class: 150, 300 PN: 10 - 100 Sizes: 3" - 96" DN: 80–600 Materials: Carbon Steel, Stainless Steel, Special Materials Body Styles: Lug, Double Flanged Short or Long

### **Features & Benefits:**

- Optimized seat angle design and Stellite® hard-faced valve body seat deliver a longer seal life and improved abrasion resistance
- Metal-to-metal sealing to deliver reliable and bidirectional shutoff
  in high-temperature, high-pressure, severe service applications, etc.
- Innovative stem seal design
- Fugitive emissions tested: ISO 15848
- Torque-seating self-adjusts to evenly distribute seal compression
- A "floating" seal ring and wide seal ring supporting gasket eliminate binding and enhance performance

Note: special configuration Turbine Trip & Throttle Valve with customized quick-closing actuation package.



## **Special Application Valves**

### **Extraction Check / Cold Reheat Non-Return Check Valves**

Brand: Krombach ASME Class: 150 - 300 PN: 16 - 40 Sizes: 6" - 72" (others upon request) DN: 150 - 1800 (others upon request) Materials: Carbon Steel, Stainless Steel Connections: Double Flanged, Weld Ends

### **Optional Features:**

- Fabricated design
- Free swinging disc
- Hardened seating surfaces
- Canted seat angle
- Hardened bushings
- Graphite packing
- Counterweights & actuation packages available
- · Customized seat diameter & disc thickness to minimize pressure drop
- Special face-to-face dimensions, flanges, and materials available
- Special approvals (ASME, CRN, IBR)

## Industrial Diaphragm Valve

Brands: Saunders Sizes: ½" - 20" Class: ASME 125-150 DN: 15-500 Materials: Cast Iron, Ductile Iron, Cast Steel, Stainless Steel, Gunmetal Linings: Glass, Rubber, Plastic Diaphragm: Rubber, PTFE Operation: Manual, Pneumatic, Electric, Hydraulic Connections: Flanged, Threaded Body Style: Weir or straight through types

### **Features & Benefits:**

- The Science Inside<sup>®</sup>: Proprietary diaphragm technology provides unique sealing solution and complete emissions control.
- Unmatched Expertise & Innovation: Comprehensive selection of polymers delivers superior corrosion and abrasion resistance for a wide range of demanding applications, since 1928.
- Efficient Operation: Top entry design enables in-line maintenance capability to reduce plant down-time.



## **Polypropylene-Lined Pipe and Fittings**



Brand: Resistoflex ASME Class: 150, 300 Sizes: 1" – 12" DN: 25 – 300 Materials: Carbon Steel, Stainless Steel Connections: Flanged



Special Configurations Available with ETFE or PVDF Liner

### **Features and Benefits:**

- Pipe and fittings liners have a heavy wall thickness and are made from raw resin at our North Carolina manufacturing facility.
- Pipe and fittings are rated for continuous full vacuum service up to 225°F
- The Resistoflex Thermalok<sup>™</sup> process locks the plastic liner in the metal housing, resulting in the liner and metal housing acting as one monolithic unit, even during frequent thermal cycling. Inherently stiff liner remains tight against the housing interior throughout its lifespan.
- Polypropylene has shown good abrasion resistance on fine slurries, such as fly ash. Third party testing indicates that Resistoflex Polypropylene liners will outperform rubber liners by a factor of four, giving enhanced service life.
- Resistoflex Polypropylene lined pipe and fittings are delivered to site ready to bolt-up, with no expensive, time-consuming, or equipment-dependent fabrication procedures.
- Polypropylene has excellent chemical resistance to a broad spectrum of acids and caustics.
- Good release properties to fight scale buildup
- Weld free construction reduces NDE costs.
- Straight lengths available up to 20 ft.
- Resistoflex pipe and fittings comply with the requirements of ASME B31.3 and ASTM F1545-15a



## **Global Coverage**



#### AMERICAS United States

Bolingbrook, Illinois Office 860 Remington Blvd. Bolingbrook, Illinois 60440 Tel: +1-630-226-4900 Fax: +1-630-226-4648 Email: sales@cranevs.com

#### **United States**

Conroe, Texas Office 9860 Johnson Road Montgomery, Texas, USA 77316 Tel: +1-936-588-8380 Fax: +1-936-588-8381

#### United States

Cullman, Alabama Office 2129 3rd Avenue SE Cullman, Alabama, USA 35055 Tel: +1-256-775-3800 Fax: +1-256-775-3860

#### **United States**

Houston, Texas Office 1202 Hahlo Street Houston, TX USA 77220 Tel: +1-713-671-4600 Fax: +1-713-671-4745

#### United States

Kennesaw, Georgia Office 2825 Cobb International Blvd. Kennesaw, GA 30152 Tel: +1-770-424-6343 Fax: +1-770-429-4750

#### **United States**

Long Beach, California Office 3201 Walnut Avenue Signal Hill, California, USA 90755 Tel: +1-562-426-2531 Fax: +1-562-595-9717 Email: pysales@craneenergy.com

#### **United States**

St. Louis, Missouri Office 3671 New Town Blvd. St. Charles, Missouri, USA 63301 Tel: +1-636-688-8750 Fax: +1-636-688-8755

#### **United States**

CRANE Energy Global Headquarters 4526 Research Forest Drive, Suite 400 The Woodlands, Texas 77381 U.S.A. Tel: +1-936-271-6500 Fax: +1-936-271-6510

#### EUROPE Belgium

Wavre, Belgium Office Avenue Franklin No. 1 B-1300 Wavre, Belgium Tel: +32-10-8184-44 Fax: +32-10-8184-58

#### Germany

Düsseldorf, Germany Office Heerdter Lohweg 63-71, D-40549 Düsseldorf, Germany Tel: +49-211-59-56-0 Fax: +49-211-59-56-111

#### Germany

Kreuztal, Germany Office Marburger Straße 364 57223 Kreuztal-Kredenbach Germany Tel: +49-0-2732-520-00 Fax: +49-0-2732-520-100 Email: krombach@craneenergy.com

#### Italy

Monza, Italy Office Via Pusiano, 2 Monza, 20052 (MI) Italy Tel: +39-039-270-4373 Fax: +39-039-270-4431

#### Russia

Moscow, Russia Office Office No. 10 Nizhniy Mezhdunarodny Pereulok, 10, Strojenie 1 Moscow 109544 Russia Tel: +7-495-9845591 Fax: +7-495-9845590

#### United Kingdom

Belfast, Ireland Office 6 Alexander Road Belfast, BT6 9HJ Northern Ireland Tel: +44-2890-704222 Fax: +44-2890-401582



## **Global Coverage**



# **Delivery Systems**

### **Original Equipment Manufacturer (OEM)**

Crane Valves Services is the OEM replacement part provider for Crane brands including Chapman and Flomatics. Our archives hold over thousands of drawings, bills of materials, material specifications and processes for valves supplied as early as the 1900's. We deliver the parts you need based on the original specifications and by using original parts your valve will have the greatest chance of functioning at its best.



## **High-Quality Manufacturing**

Using high-quality materials, state-of-the-art processes and ultra-modern machining equipment, Crane Valve Services reproduce parts to match the original print. The end result is reliability you can count on for years to come.

### **Valve Experts**

Through our national network of service centers and authorized repair centers, our team of factory trained professionals offers expert, dependable repair and reconditioning work, fast turnaround and warranted performance on just about any valve. Call one of our expert part specialists today to help with all your OEM needs.





## Delivered Fast Using QuickShipSM

To meet our customers' urgent requirement for replacement parts, Crane Valve Services has developed a program called QuickShipSM. This program is designed so that many replacement parts can be shipped in days or expedited to meet your particular needs.



# Notes



CRANE ChemPharma & Energy Global Headquarters 4526 Research Forest Drive, Suite 400 The Woodlands, Texas 77381 U.S.A. Phone: (1) 936-271-6500 Fax.: (1) 936-271-6510 www.cranecpe.com

> CRANE Valve Services 860 Remington Boulevard Bolingbrook, Illinois 60440 Phone: (1) 800-272-6315 Fax: (1) 630-226-4646 Email: sales@cranevs.com



Crane Co., and its subsidiaries cannot accept responsibility for possible errors in catalogues, brochures, other printed materials, and website information. Crane Co. reserves the right to alter its products without notice, including products already on order provided that such alteration can be made without changes being necessary in specifications already agreed. All trademarks in this material are property of the Crane Co. or its subsidiaries. The Crane and Crane brands logotype, in alphabetical order, (ALOYCO<sup>o</sup>, CENTER LINE<sup>o</sup>, COMPAC-NOZ<sup>o</sup>, CRANE<sup>o</sup>, DEPA<sup>o</sup>, DUO-CHEK<sup>o</sup>, FLOWSEAL<sup>o</sup>, JENKINS<sup>o</sup>, KROMBACH<sup>o</sup>, NOZ-CHEK<sup>o</sup>, PACIFIC VALVES<sup>o</sup>, RESISTOFLEX<sup>o</sup>, REVO<sup>o</sup>, SAUNDERS<sup>o</sup>, STOCKHAM<sup>o</sup>, TRIANGLE<sup>o</sup>, UNI-CHEK<sup>o</sup>, WTA<sup>o</sup>, and XOMOX<sup>o</sup>) are registered trademarks of Crane Co. All rights reserved.

© Crane ChemPharma & Energy