


DN80 TO DN100
MAINLINE ONLY



ORIENTATION AS
PER P&ID DIAGRAM
FOR OPTIMUM
DRAINABILITY.

| MAINLINE SIZE | A | B | C | D | ϕE | ϕF | G | BODY WEIGHT |
|--------------------|-------|------|------|------|----------|----------|------|-------------|
| mm | mm | mm | mm | mm | mm | mm | mm | Kgs |
| DN80 DIN 11850 S1 | 50.8 | 50.8 | 48.5 | 67.0 | 85.0 | 81.0 | 45.5 | 17.2 |
| DN100 DIN 11850 S1 | 101.6 | 50.8 | 58.0 | 77.0 | 104.0 | 100.0 | 45.5 | 22.4 |

The information on this sheet is Private and Confidential and is the property of Crane Process Flow Technologies Limited and must not be published directly or indirectly in any manner whatsoever without the written permission of the Company and must not be used in any way detrimental to their interests.
© Crane Process Flow Technologies



Title
SCHEDULE OF LEADING DIMENSIONS FOR DN80 WEIR
'T' BODY WITH DIN 11850 S1 BUTT WELD ENDS

| | | | |
|---------------------------------------|-----------------|-------------------------------------|-------------|
| Drawn R1 | Date 11.11.11 | UNCONTROLLED IN HARD COPY FORMAT | |
| Checked RND | Date 02.04.12 | | |
| First Angle Projection Method E | DO NOT SCALE | Drawing No. WEB-104 | Issue. 2 |