


	VALVE	Α		В		С		₩E I GHT
SIZ	∠Ł	mm	inch	mm	inch	mm	inch	KGS
DN50 S	C LITE	332	13.07	95	3.74	123	4.84	8,4
DN50	SO	341	13.43	95	3.74	150	5.91	10.4
DN50	DA	341	13,43	95	3.74	150	5.91	10.1
DN50 S	C POWER	341	13.43	95	3.74	150	5,91	10.4











DN50 S360 Ø125 PISTON SPRING OPENING/DOUBLE ACTING





DN50 POWER S360 Ø125 PISTON SPRING CLOSING

The information on this sheet is Private and Confidential and is the property of Crane Process Flow Technologies Limited and must not be published directly or indirectly in any monner whatsoever without the written permission of the Company and must not be used in any way detrimental to their interests.

© Crane Process Flow Technologies

CRANE Process Flow Technologies
A Crane Co. Company

Title

LEADING DIMENSIONS FOR DN50 Ø100/125 PISTON ACTUATORS FITTED WITH MODULE SWITCHBOXES

	Drawn NAW	Date 29.08.12		UNCONTROLLED IN		
ſ	CheckedRND	Date 29	.08.12	HARD COPY FORMAT		
-	First Angle Projection Method E	} 	DO NOT SCALE	Drawing No. WEB-242	Issue. 1	